Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: NUD COLLECTION

Supplier's address: Product Development, Trumslagar Blomgrens väg 4, SE

Model identifier: 911364-3D

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	Amber, E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	Yes	Dimmable:	Yes		
Product parameters					

Parameter		Value	Parameter	Value
		General product p		
Energy consum mode (kWh/100 up to the nearest	0 h), rounded	4	Energy efficiency class	G
Useful luminous indicating if it ref in a sphere (360 cone (120 ^o) or in (90 ^o)	fers to the flux D ^o), in a wide	120 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1 800
On-mode po expressed in W	ower (P _{on}),	4,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,10
Networked stand for CLS, express rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80
Outer	Height	145	Spectral power	See image
	Width	64	distribution in the	in last page
without	Depth	145	1	 Page 1 / '

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,543			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	0,00			
the lumen maintenance factor	0,95					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'_-' : not applicable;

