## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		, , ,	_			
Supplier's name or trade mark: AYTM						
Supplier's address: AYTM, Polensgade 15, 8000 Aarhus, DK						
Model identifie	r: Castellum LED	lamp				
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		socket				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		Yes	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		11	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		455 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 844		
On-mode power (P <sub>on</sub> ), expressed in W		11,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,10		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,10	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	94		
Outer	Height	182	Spectral power	See image		
dimensions without	Width	55	distribution in the	in last page		
	Depth	110		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,446		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	72	Survival factor	-		
the lumen maintenance factor	-				

(a)'-': not applicable; (b)'-': not applicable;

## **Test Condition**

Temperature: °C

Spectrum Range: 380-800 nm

RH: % Scan Step: 5 nm

## **Spectroradiometric Parameters**



